



ELEMENT VENEER SPECIFICATIONS

Name: Element Veneer
Panel Size: 4' x 8' and 4' x 10' available
Thickness: 0.5mm or .02"
Backing: Paper back or raw
Edgetape: Matching 0.5mm and 2mm in stock
Certification: FSC® Certified

Custom Lay-up Available

Lead Times: Allow 1–2 weeks
Grain Options: 4 x 8, 8 x 4, 4 x 10, 10 x 4
Grain Cut: Straight grain, Rift cut

Colour Options:

Charcoal Ash	UC3004	Rift White Oak	UC3008
Driftwood	UC3010	Quartered Teak	UC3013
Silver Elm	UC3006	Claro Walnut	UC3007
Coastal VG Fir	UC3000	Quartered Walnut	UC3002
European Oak	UC3012	Quartered Wenge	UC3009
Black Oak	UC3011	Platinum Wenge	UC3003
Frosted Oak	UC3001		

Cores: MDF, PB, MDX
Thickness: 5.2mm to 1 1/2"
Certification of Core: CARB2, FSC® Mix Credit, NAF, NAUF or ULEF (Varies by cores selected)

Element Veneer Specification Usage and Specification Guide:

- 1) Element Veneer is real wood and should be treated and processed as you would other real wood products.
- 2) Only clear finishes, preferably with a UV inhibitor, are recommended.
- 3) Backer/Substrate is required and can include medium density fibreboard (MDF), particleboard (PBC), cross banded MDF (MDX) and veneer quality plywood.
- 4) When bonding Element Veneer to a substrate please follow the directions of the adhesive manufacturer.
Laid-up panels are available directly from Sierra.
- 5) FSC® is available upon request.



Upper Canada Forest Products
1 866 265 0624 | www.ucfp.com

Toronto sales_toronto@ucfp.com
Edmonton sales_edmonton@ucfp.com
Calgary sales_calgary@ucfp.com
Kelowna sales_kelowna@ucfp.com
Vancouver sales_vancouver@ucfp.com
Victoria sales_victoria@ucfp.com